



More than colour

## CHROMATIC 2 PACK EXTERIOR VARNISH

**PRODUCT DESCRIPTION AND USES:**

Chromatic 2 pack Exterior Varnish is a two-pack product where drying is achieved from the chemical reaction between the two components, giving a hard, mark proof film with good wear and chemical resistance.

**FINISH:**

High Gloss and matt

**APPLICATION:**

By Brush, Spray

**MIXING RATIO:**

3 parts of Base: 1 part Hardener by Volume.

**THINING:**

Normally thinning is not required after mixing the Base and the Hardener. However, for ease of application, up to 5% of two pack polyurethane Thinner may be added to the mixture of base and hardener.

**EQUIPMENT CLEANING:**

Clean equipment with Chromatic Two Pack Polyurethane Thinner immediately after use.

**DRYING TIME:**

Surface Dry in 2 hours, Recoatable in 14 hours

**COLOUR RANGE:**

Clear and a few selected shades

**SPREADING CAPACITY:**

15 - 16m<sup>2</sup> per litre depending on surface porosity

**PACK SIZES:**

3 litres

**SPECIFICATION:**

Brushes or spray equipment must be thoroughly clean and dry before use. Though the mixture of Chromatic Two Pack Exterior Varnish and Hardner has a fairly long pot-life, it is advisable that only enough mixture for the job at hand should be mixed. Avoid using the mixture after 8 hours as the effectiveness will have reduced.

**PRECAUTION:**

- I. Always ensure good ventilation when applying Chromatic 2 pack PU varnish
- II. On all surfaces, heavy traffic should be permitted only after 7 days of drying. Light traffic may be allowed after 24 hours of drying.
- III. Chromatic 2 pack Exterior varnish contains inflammable solvents, therefore smoking or use of naked flames must be prohibited when application is in progress.

## DISCLAIMER

The recommendations contained herein are given in good faith and meant to guide the user in accordance with good painting practices. They are gained from our tests and experiences and are believed to be accurate and reliable.

No warranty/guarantee is implied by the recommendations contained herein since the conditions of use; application method, substrate and cleanliness of the substrate are beyond the control of Chromatic Paints Uganda.

Technology may change with time, necessitating changes to this Technical Data Sheet (TDS). Chromatic Paints Uganda reserves the right to amend the TDS without any further notice. It is the responsibility of the user to ensure that the latest TDS is being used for reference

For health & safety information, please refer to our Material Safety Data Sheet (MSDS)

