

CHROMATIC 2K ACRYLIC THINNER

PRODUCT DESCRIPTION AND

USES:

Chromatic 2K Acrylic thinner is a clear blend of organic solvents used for thinning automotive 2K Acrylic based primers

and enamels

ADVANTAGES: High solvent power

COLOUR RANGE: Clear

ODOUR: Characteristic of aromatics, esters and ketones

PRECAUTIONS: Ensure containers are tightly closed to minimize evaporation.

PACK SIZES: 1L & 5L

MIXING RATIO: As directed on product being thinned

STORAGE CONDITIONS: Avoid direct contact with the substance.

Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Avoid the formation or spread of mists in

the air.

Smoking is forbidden while using the product.

Conditions for safe storage, including any incompatibilities Storage conditions: Store in a cool, well-ventilated area. Keep container tightly closed. Keep away from sources of ignition.

HEALTH AND SAFETY: Repeated exposure may cause skin dryness or cracking.

Highly flammable liquid and vapour.

May be fatal if swallowed and enters airways.

Causes skin irritation.

Causes serious eye damage.

May cause drowsiness or dizziness.

May cause damage to organs through prolonged or repeated exposure. Repeated exposure may cause skin dryness or

cracking. Highly flammable liquid and vapour.

Causes serious eye damage.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. Description of first aid measures Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water. Eye contact: Bathe the eye with

running water for 15 minutes.

DISCLAIMER

The recommendations contained herein are given in good faith and meant to guide the user in accordance with good painting practices. They are gained from our tests and experiences and are believed to be accurate and reliable.

No warranty/guarantee is implied by the recommendations contained herein since the conditions of use; application method, substrate and cleanliness of the substrate are beyond the control of Chromatic Paints Uganda.

Technology may change with time, necessitating changes to this Technical Data Sheet (TDS). Chromatic Paints Uganda reserves the right to amend the TDS without any further notice. It is the responsibility of the user to ensure that the latest TDS is being used for reference

For health & safety information, please refer to our Material Safety Data Sheet (MSDS)







