

CHROMATIC ACRYLIC FLOORCOAT PAINT

PRODUCT DESCRIPTION AND USES:	Chromatic Acrylic FloorCoat Paint is a self-priming pure acrylic co polymer-based emulsion paint that protects and transforms interior & exterior floors, with an attractive, tough, durable, and easy to clean coating. Due to its excellent adhesion, Durable finish, Low glare matt finish, resistance to abrasion and scuffing, low Odor, great opacity, quick drying and weathering properties it is ideal for domestic, commercial and light industrial use.
SUBSTRATE:	Concrete floorsPlay courts
SURFACE PREPARATION:	Ensure surface is clean, dry and free dust, dirt, grease or wax. New smooth cement floors: must be etched with Chromatic Etch solution before paint application. First coat to be thinned more than subsequent coats to facilitate firm adhesion. Old, chalky/unsound surfaces: must be well sanded and cleaned to remove any loose material, two coats of Chromatic Acrylic FloorCoat Paint can then be applied allowing 2-4 hours between coats. The first coat should be very thin for proper adhesion
FINISH:	Low sheen smooth finish
APPLICATION:	By brush or roller.
DRYING TIME:	2-4 hours in dry conditions. (Weather and ventilation to be put into consideration.)
COLOUR RANGE:	In over 3000 colours.
SPREADING CAPACITY:	9-10m ² per litre However spreading rate depending porosity and profile of the surface
PACK SIZES:	20 litres, 4 litres and 1 litre.
THINNING & MIXING:	Clean water
EQUIPMENT CLEANER:	Water

DISCLAIMER

The recommendations contained herein are given in good faith and meant to guide the user in accordance with good painting practices. They are gained from our tests and experiences and are believed to be accurate and reliable.

No warranty/guarantee is implied by the recommendations contained herein since the conditions of use; application method, substrate and cleanliness of the substrate are beyond the control of Chromatic Paints Uganda.

Technology may change with time, necessitating changes to this Technical Data Sheet (TDS). Chromatic Paints Uganda reserves the right to amend the TDS without any further notice. It is the responsibility of the user to ensure that the latest TDS is being used for reference

For health & safety information, please refer to our Material Safety Data Sheet (MSDS)

