



More than colour

CHROMATIC ACRYLIC MATT EMULSION

PRODUCT DESCRIPTION AND USES:

Chromatic acrylic matt emulsion is a uniquely formulated coating based on an acrylic copolymer emulsion. With its excellent flexibility, toughness, abrasion resistance and low dust retention properties, chromatic acrylic matt emulsion is a perfect finish for interior walls that require a high quality low sheen finish. It contains additional biocides to combat attack from mould and algae. Its unique formulation and smooth finish makes it the preferred product for hotels, homes, offices, schools and all other interior wall needs.

SURFACE PREPARATION:

New Substrate;
Must be clean, dry and free of loose materials. Apply 1 coat of Chromatic Plaster primer or 02 Coats of Chromatic Budget Matt emulsion Undercoat, followed by 2-3 coats of chromatic acrylic matt emulsion.

Chalky/Powdery or Flaking surfaces
Use a nylon brush to remove loose and flaking materials. Apply 1 coat of Chromatic penetrating primer. Finish with 2 coats of chromatic acrylic matt emulsion paint.

Previously painted surfaces in sound condition.
Sand down the existing coat to a firm base. Then apply two coats of chromatic acrylic matt emulsion. Allow 4 hours between coats

FINISH:

Low sheen

APPLICATION:

By brush, roller or airless spray

THINNING & MIXING:

Thin with clean tap water.

EQUIPMENT CLEANING:

Clean the equipment with water.

DRYING TIME:

4 hours

COLOUR RANGE:

Available in over 3000 Chromatic In house shades and BS4800 Colour range

SPREADING CAPACITY:

11-14 m² per litre at 40 microns DFT

PACK SIZES:

1 Litre, 4 Litres and 20 Litres

DISCLAIMER

The recommendations contained herein are given in good faith and meant to guide the user in accordance with good painting practices. They are gained from our tests and experiences and are believed to be accurate and reliable.

No warranty/guarantee is implied by the recommendations contained herein since the conditions of use; application method, substrate and cleanliness of the substrate are beyond the control of Chromatic Paints Uganda.

Technology may change with time, necessitating changes to this Technical Data Sheet (TDS). Chromatic Paints Uganda reserves the right to amend the TDS without any further notice. It is the responsibility of the user to ensure that the latest TDS is being used for reference

For health & safety information, please refer to our Material Safety Data Sheet (MSDS)

