



More than colour

## CHROMATIC ACRYLIC ROOFCOAT PAINT

### PRODUCT DESCRIPTION AND USES:

Chromatic Acrylic RoofCoat Paint is a premium quality UV resistant water based, self-priming pure acrylic co polymer-based emulsion paint. It protects and transforms roofs with an attractive, tough, and durable coating. Chromatic Acrylic RoofCoat is a weather resistant, and with long lasting colour protection. It rejuvenates and restores old roofs.

Chromatic Acrylic RoofCoat is a flexible coating designed for application to new and previously painted (sound) roofs, walls and masonry. It is suited for application to asphalt and bituminous emulsion coated surfaces in addition to concrete, brick, asbestos, cement, weathered GCI and aluminium etc.

### SURFACE PREPARATION:

Ensure roof is dry, dust free and in sound structural condition. Apply 2 coat of chromatic acrylic RoofCoat paint. The first to be thinned on a ratio of 1:1 (paint to water) and subsequent coat thinned to 2:1 (paint:water).

Prior to application of Chromatic Acrylic RoofCoat to asphalt and bitumen emulsion surfaces, ensure that the substrate is clean and dust free and in sound structural condition. When coating flat roof surfaces, ensure that all surface rainwater is thoroughly removed and the surface allowed drying out. The substrate may be damp but there must be no actively percolating water.

### FINISH:

Low sheen

### APPLICATION:

By brush or roller. Can be applied by spray equipment if necessary for best results application of 2 coats of RoofCoat is recommended.

### DRYING TIME:

Re-coatable after 3-4 hours in dry conditions. (Weather and ventilation to be put into consideration.)

### COLOUR RANGE:

In over 3000 colours.

### SPREADING CAPACITY:

9-10m<sup>2</sup> per litre However spreading rate depending porosity and profile of the surface

### PACK SIZES:

20 litres, 4 litres and 1 litre.

### THINNING & MIXING:

Clean water

## DISCLAIMER

The recommendations contained herein are given in good faith and meant to guide the user in accordance with good painting practices. They are gained from our tests and experiences and are believed to be accurate and reliable.

No warranty/guarantee is implied by the recommendations contained herein since the conditions of use; application method, substrate and cleanliness of the substrate are beyond the control of Chromatic Paints Uganda.

Technology may change with time, necessitating changes to this Technical Data Sheet (TDS). Chromatic Paints Uganda reserves the right to amend the TDS without any further notice. It is the responsibility of the user to ensure that the latest TDS is being used for reference

For health & safety information, please refer to our Material Safety Data Sheet (MSDS)

