

CHROMATIC ALKALI RESISTANT PRIMER

PRODUCT DESCRIPTION AND USES:	Chromatic Alkali Resistant Primer/Sealer is based on cyclized rubber and designed for use on new and bare alkaline surfaces e.g. plaster, cement, concrete, hard asbestos sheets etc., prior to the application of oil-based paints. It seals new plaster before the application of an undercoat or finishing coat. Should not be used for under bound or flaking surfaces. It protects the coat of subsequent paint from saponification and discoloration.
SURFACE PREPARATION:	For New and unpainted plaster, cement, stone, brick etc., ensure the surface is clean and dry. Apply one coat of Alkali Resistant Primer Sealer . Allow to dry thoroughly for 24 hours
FINISH:	Matt
APPLICATION:	By brush or roller
THINING & MIXING:	Chromatic White Spirit
EQUIPMENT CLEANING:	Clean equipment immediately after use with Chromatic White Spirit.
DRYING TIME:	Recoatable after 16 hours.
COLOUR RANGE:	Off White
SPREADING CAPACITY:	Approximately 10 - 12m ² per litre on smooth, steel float plaster. The spreading capacity will be considerably reduced when applied to rough or porous surfaces.
PACK SIZES:	1 Litre, 4 Liters, 20 Liters



DISCLAIMER

The recommendations contained herein are given in good faith and meant to guide the user in accordance with good painting practices. They are gained from our tests and experiences and are believed to be accurate and reliable.

No warranty/guarantee is implied by the recommendations contained herein since the conditions of use; application method, substrate and cleanliness of the substrate are beyond the control of Chromatic Paints Uganda.

Technology may change with time, necessitating changes to this Technical Data Sheet (TDS). Chromatic Paints Uganda reserves the right to amend the TDS without any further notice. It is the responsibility of the user to ensure that the latest TDS is being used for reference

For health & safety information, please refer to our Material Safety Data Sheet (MSDS)

