

CHROMATIC ANTIFUNGAL SOLUTION

PRODUCT DESCRIPTION AND USES:	Chromatic antifungal solution is a specially made solution with an efficient preservative against a wide variety of fungal organisms (mould, stain and mildew)
SPREADING CAPACITY:	5 - 8 m²/Lt
THINNING:	Supplied ready for use. Do not thin.
APPLICATION METHOD:	Clean surfaces of all loose & flaking paint. Apply on areas where there is fungus growth and leave for 5 hours and scrap off the fungus. (Note: Burn scrapings off site). Apply second coat of antifungal solution while leave overnight (do not scrap off) and paint over the surface.
APPLICATION:	By brush only
EQUIPMENT CLEANER:	Water
PACK SIZES:	1L & 5L

DISCLAIMER

The recommendations contained herein are given in good faith and meant to guide the user in accordance with good painting practices. They are gained from our tests and experiences and are believed to be accurate and reliable.

No warranty/guarantee is implied by the recommendations contained herein since the conditions of use; application method, substrate and cleanliness of the substrate are beyond the control of Chromatic Paints Uganda.

Technology may change with time, necessitating changes to this Technical Data Sheet (TDS). Chromatic Paints Uganda reserves the right to amend the TDS without any further notice. It is the responsibility of the user to ensure that the latest TDS is being used for reference

For health & safety information, please refer to our Material Safety Data Sheet (MSDS)

