

## **CHROMATIC BUDGET HIGH GLOSS PAINT**

PRODUCT DESCRIPTION AND USES:

Chromatic Budget High Gloss Paint is a highly durable synthetic enamel paint ideal for use on interior and exterior wood, brick and stone work and metallic surfaces. It is economical and easy to apply. It is applied over suitably primed surfaces

**SURFACE PREPARATION:** 

**PRIMING:** 

New surfaces; Prepare surface (refer appropriate surface preparation Data Sheet). Apply 1 coat appropriate Primer. Apply 2 coats Chromatic Budget Gloss.

Previously Painted Surfaces-Sound Condition: Prepare surface. Apply 1 coat of Chromatic Universal undercoat (Where necessary only). Apply 2-3 coats of Chromatic Budget Gloss paint

Previously Painted Surfaces-unsound Condition: Remove all old loose, flaking and wrinkled oil paint using paint scrapers/sandpaper or by mechanical means, down to the original surface where necessary. Patch prime (bare metal, wood plaster surfaces) with appropriate primer. Apply 1 coat Chromatic Universal Undercoat. Apply 2-3 coats of Chromatic Budget High Gloss paint.

In order to obtain the best results, it is recommended that the surface be primed as follows:

On new wood use Chromatic Wood Primer, on steel use Chromatic Zinc Phosphate Primer or Chromatic Red Oxide Primer. On galvanized steel use zinc and light alloy metals only Chromatic Wash Primer (two pack etch primer) is

recommended. If undercoating is desired use Chromatic

Budget Undercoat.

**APPLICATION:** Apply by brush, roller or spray

**DRYING TIME:** Touch Dry:4hrs Hard Dry:24 hrs. Recoatable after 16 hours.

FINISH: Glossy

**THINNING:** Thin with white spirit

**EQUIPMENT CLEANING:** Clean the equipment immediately after use with White spirit.

**PACK SIZES:** 1/4L.1/2L,1L 4L and 20L

## **DISCLAIMER**

The recommendations contained herein are given in good faith and meant to guide the user in accordance with good painting practices. They are gained from our tests and experiences and are believed to be accurate and reliable.

No warranty/guarantee is implied by the recommendations contained herein since the conditions of use; application method, substrate and cleanliness of the substrate are beyond the control of Chromatic Paints Uganda.

Technology may change with time, necessitating changes to this Technical Data Sheet (TDS). Chromatic Paints Uganda reserves the right to amend the TDS without any further notice. It is the responsibility of the user to ensure that the latest TDS is being used for reference

For health & safety information, please refer to our Material Safety Data Sheet (MSDS)







