



More than colour

## CHROMATIC BUDGET UNDERCOAT WHITE

### PRODUCT DESCRIPTION AND USES:

Chromatic Budget Undercoat Emulsion is a copolymer based emulsion suitable for interior and exterior applications used as an adhesion medium for subsequent coats. It has excellent hiding power and presents a matt finish. It can be used on cementitious surfaces, lime, plaster, as well as stone and blocks and it is economical on new surfaces

### SURFACE PREPARATION:

Surfaces to be painted must be clean and dry. No under bound or loose materials should be left prior to painting. Under bound and chalky surfaces can be treated with one coat of Chromatic penetrating primer

**New surfaces:** Remove all nibs, efflorescence and loose materials. Dust off and fill small imperfections with Chromatic Skim Putty. Smooth down and ensure the surface is clean and dry. Apply 2 coats of Chromatic Budget Undercoat Emulsion thinned with water to normal working consistency.

**Previously painted - sound:** Sand down to form a key for subsequent coats. Remove all loose and flaky material by scraping or by use of a stiff fiber or nylon brush. Make good any minor imperfections with Chromatic Skim Putty. Ensure the surface is clean and dry. Apply 2 coats of Chromatic Budget Undercoat Emulsion thinned with water to normal working consistency.

**Previously Painted-Unsound:** Remove all loose and flaking materials including old distemper, lime wash or old paint, down to a firm base. Ensure the surface is clean and dry before application of one coat of Chromatic Penetrating Primer to bind and seal the surface. Apply 2 coats of Chromatic Budget Undercoat Emulsion, thinned with water to normal working consistency.

### DRYING TIME:

Recoatable after 4 hours

### FINISH:

Matt

### THINNING & MIXING:

Thin with clean tap water to normal working consistency

### SPREADING CAPACITY:

6 to 8 M<sup>2</sup> per coat depending on the nature of the surface.

### PACKING:

Available in 4ltrs and 20ltrs

### COLOUR RANGE:

White

## DISCLAIMER

The recommendations contained herein are given in good faith and meant to guide the user in accordance with good painting practices. They are gained from our tests and experiences and are believed to be accurate and reliable.

No warranty/guarantee is implied by the recommendations contained herein since the conditions of use; application method, substrate and cleanliness of the substrate are beyond the control of Chromatic Paints Uganda.

Technology may change with time, necessitating changes to this Technical Data Sheet (TDS). Chromatic Paints Uganda reserves the right to amend the TDS without any further notice. It is the responsibility of the user to ensure that the latest TDS is being used for reference

For health & safety information, please refer to our Material Safety Data Sheet (MSDS)

