



More than colour

## CHROMATIC EGGSHELL ENAMEL

**PRODUCT DESCRIPTION AND USES:**

Chromatic Eggshell enamel is a semi - gloss alkyd-based finish that uses light fast pigments. Its washability, durability and dirt resistance properties makes it ideal for walls of high traffic areas, ceilings, wood and metal works. Its semi-gloss or low sheen finish gives it an exceptionally rich and thin finish.

**SURFACE PREPARATION:**

New surfaces: Surfaces should be clean, dry and free of any loose and flaky materials. Apply one coat of Chromatic universal undercoat. Then apply two coats of Chromatic eggshell enamel paint. Sand lightly between coats. Allow overnight drying between each coat.

Previously painted walls: Ensure the surface is clean, dry and free from loose and flaky materials. In case of unsound/loose surfaces, apply one coat of Chromatic penetrating primer. Apply one coat of Chromatic universal undercoat. Apply two coats of Chromatic Eggshell Enamel Paint. Sand lightly between coats. Allow overnight drying between coats

**APPLICATION:**

Apply by brush, roller or spray

**DRYING TIME:**

Touch dry 4 hours. Re-coatable after 16 hours

**FINISH:**

Semi-gloss.

**THINNING & MIXING:**

Thin with white spirit for brush or roller application and with Chromatic Enamel thinner for spray applications. Thinning ratio is 12 - 20%. Note: avoid over-thinning as this affects hiding power.

**EQUIPMENT CLEANING:**

Clean the equipment immediately after use with White spirit.

**SPREADING CAPACITY:**

12 - 14 m<sup>2</sup> per litre on a smooth surface at 30/40 microns DFT.

**COLOUR RANGE:**

Available in Brilliant white, shades from the BS 4800 colours

**PACK SIZES:**

1ltr ,4 litres, 20 litres

## DISCLAIMER

The recommendations contained herein are given in good faith and meant to guide the user in accordance with good painting practices. They are gained from our tests and experiences and are believed to be accurate and reliable.

No warranty/guarantee is implied by the recommendations contained herein since the conditions of use; application method, substrate and cleanliness of the substrate are beyond the control of Chromatic Paints Uganda.

Technology may change with time, necessitating changes to this Technical Data Sheet (TDS). Chromatic Paints Uganda reserves the right to amend the TDS without any further notice. It is the responsibility of the user to ensure that the latest TDS is being used for reference

For health & safety information, please refer to our Material Safety Data Sheet (MSDS)

