



More than colour

CHROMATIC EPOXY FLOOR PAINT

PRODUCT DESCRIPTION AND USES:

Chromatic Epoxy Floor is a two-pack component paint based on Epoxy resin. It offers excellent adhesion onto concrete, cement and nonferrous metals. It is a hard wearing paint that provides excellent resistance to water, solvents, acids, alkalis and salts. Chromatic epoxy floor paint gives superb adhesion, long lasting chemical, abrasion, water and impact resistance. It gives a superb gloss finish that makes it easy to maintain. Recommended for areas receiving heavy foot and vehicle traffic.

SURFACE PREPARATION:

New or old concrete floors must be clean from all contaminants. Smooth surfaces must be etched with Chromatic etch solution, rinsed with soapy water and dried thoroughly well before paint application. Firstcoat thinned more than the subsequent coats for firm adhesion

FINISH:

Gloss

APPLICATION:

By brush or Roller

DRYING TIME:

touch dry in 2 hours, thorough dry in 24 hours. Maximum hardness is achieved after 3 days.

COLOUR RANGE:

Available in smoke Grey, Black, and Red Oxide. (Other colours on request)

SPREADING CAPACITY:

8 -10 square meters per liter.

PACK SIZES:

1 litre, 4 litre

THINNING & MIXING:

Mix with Chromatic Epoxy Floor hardener: 3 parts to 1-part (3:1) paint to hardener and thin with Chromatic Epoxy thinner. Use the mixture within 8 hours because of limited pot life

EQUIPMENT CLEANING:

Chromatic Epoxy Thinner

POT LIFE:

6-8 hours

N.B.

Care should be taken to ensure complete ventilation and a mask should be worn in confined spaces. DO NOT mix more than can be used within 8 hours.

DISCLAIMER

The recommendations contained herein are given in good faith and meant to guide the user in accordance with good painting practices. They are gained from our tests and experiences and are believed to be accurate and reliable.

No warranty/guarantee is implied by the recommendations contained herein since the conditions of use; application method, substrate and cleanliness of the substrate are beyond the control of Chromatic Paints Uganda.

Technology may change with time, necessitating changes to this Technical Data Sheet (TDS). Chromatic Paints Uganda reserves the right to amend the TDS without any further notice. It is the responsibility of the user to ensure that the latest TDS is being used for reference

For health & safety information, please refer to our Material Safety Data Sheet (MSDS)

