



More than colour

CHROMATIC EPOXY ZINC PHOSPHATE PRIMER

PRODUCT DESCRIPTION AND USES:

Chromatic Epoxy Zinc Phosphate Primer is a superior quality, 2-component (base and hardener) based on epoxy resin pigmented with Zinc Phosphate anti-corrosive pigment. The product has great anti rust power, very good hardness, adhesion, flexibility, very good filling power, opacity, high resistance to chemical abrasion and water. Chromatic Epoxy Zinc Phosphate Primer improves adhesion of topcoats and resists moisture damage caused by water permeation.

SURFACE PREPARATION:

The surface must be free from grease and oil. Remove by sanding, etching, scraping or sand blasting, all traces of rust, grease, oil and all contaminants that might interfere with adhesion. Prior to use, mix 3 parts base to 1 part curing agent by volume, stirring thoroughly. Can be thinned with Chromatic Epoxy Thinner if necessary to ease brushing and for spray application. Allow the mixed material to stand for 15 minutes prior to use. The mixture must be used within 8 hours of mixing the components.

ADVANTAGES:

Quick Drying. Excellent adhesion and corrosion resistance. Exceptional top coat hold-out.

EQUIPMENT CLEANING:

chromatic Epoxy Thinner.

APPLICATION:

By brush, spray or roller.

POT LIFE:

Approximately 8 hours. Only mix when surface is ready for application

DRYING TIME:

Sand dry 2-4 hours; thorough dry 24 hours.

FINISH:

Matt

COLOUR RANGE:

Light grey

SPREADING CAPACITY:

6-8 m² per litre mixed components at 50 microns DFT.

PACK SIZES:

1 Litre, 4 Liters

ATTENTION:

Ample ventilation to be provided when applying in confined spaces and a mask to be worn when spraying.

DISCLAIMER

The recommendations contained herein are given in good faith and meant to guide the user in accordance with good painting practices. They are gained from our tests and experiences and are believed to be accurate and reliable.

No warranty/guarantee is implied by the recommendations contained herein since the conditions of use; application method, substrate and cleanliness of the substrate are beyond the control of Chromatic Paints Uganda.

Technology may change with time, necessitating changes to this Technical Data Sheet (TDS). Chromatic Paints Uganda reserves the right to amend the TDS without any further notice. It is the responsibility of the user to ensure that the latest TDS is being used for reference

For health & safety information, please refer to our Material Safety Data Sheet (MSDS)

