



More than colour

CHROMATIC FAST DRY

PRODUCT DESCRIPTION AND USES:

Chromatic Fast Dry is a highly durable alkyd-based fast drying synthetic enamel paint, which is very easy to apply. It is ideal for all painting interior and exterior wood, metal, vehicles. It is highly recommended on substrate where high quality finishes are required.

SURFACE PREPARATION:

On new wood, apply chromatic Wood Primer; on steel apply the appropriate primer. On galvanized steel, Zinc and light alloy metals only chromatic 2pack zinc chromate Primer is recommended

FINISH:

Gloss

APPLICATION:

Brush, roller or spray

THINING:

For brush application thin with Chromatic white spirit. For spray application, thin with high gloss Thinner

DRYING TIME:

Touch dry is 30 minutes. Recoatable after 2 hours

COLOUR RANGE:

Available in selected Chromatic colours

SPREADING CAPACITY:

Approximately 12M² to 14M² per litre but can vary depending on the surface texture and porosity

PACK SIZES:

1 litre, 4 litres

DISCLAIMER

The recommendations contained herein are given in good faith and meant to guide the user in accordance with good painting practices. They are gained from our tests and experiences and are believed to be accurate and reliable.

No warranty/guarantee is implied by the recommendations contained herein since the conditions of use; application method, substrate and cleanliness of the substrate are beyond the control of Chromatic Paints Uganda.

Technology may change with time, necessitating changes to this Technical Data Sheet (TDS). Chromatic Paints Uganda reserves the right to amend the TDS without any further notice. It is the responsibility of the user to ensure that the latest TDS is being used for reference

For health & safety information, please refer to our Material Safety Data Sheet (MSDS)

