



More than colour

CHROMATIC FLOORCOAT PAINT

PRODUCT DESCRIPTION AND USES:

Chromatic FloorCoat paint is a single pack solvent based floor coating formulated with flexible alkyd and light fast pigments to protect and transform interior and exterior floors. It is designed for concrete, timber, stone and brick floors. With an attractive, tough, fashionable and easy to clean coating, Chromatic FloorCoat is formulated to provide abrasion resistance, first class adhesion, flexibility and durability to withstand our tropical climate.

SURFACE PREPARATION:

Ensure surface is totally clean, dry, grease or wax free for adhesion purposes.

New smooth cement floors: must be etched with Chromatic Etch solution before paint application. Apply two coats of Chromatic FloorCoat paint. First coat to be thinned more than subsequent coats.

Old, chalky/unsound surfaces: must be well sanded and cleaned to remove any loose material. Two coats of Chromatic FloorCoat Paint can then be applied allowing 2-4 hours between coats. The first coat should be thinned more for proper adhesion.

FINISH:

Gloss

APPLICATION:

By brush or roller.

DRYING TIME:

Touch dry is 4 hours. Recoat after 14 hours. (weather and ventilation to be put into consideration.)

COLOUR RANGE:

In over 3000 colours

SPREADING CAPACITY:

10-12m² per litre However spreading rate depending porosity and profile of the surface.

PACK SIZES:

20 litres, 4 litres and 1 litre.

THINNING & MIXING:

Chromatic White spirit

EQUIPMENT CLEANER:

Clean with Chromatic white spirit immediately after use

DISCLAIMER

The recommendations contained herein are given in good faith and meant to guide the user in accordance with good painting practices. They are gained from our tests and experiences and are believed to be accurate and reliable.

No warranty/guarantee is implied by the recommendations contained herein since the conditions of use; application method, substrate and cleanliness of the substrate are beyond the control of Chromatic Paints Uganda.

Technology may change with time, necessitating changes to this Technical Data Sheet (TDS). Chromatic Paints Uganda reserves the right to amend the TDS without any further notice. It is the responsibility of the user to ensure that the latest TDS is being used for reference

For health & safety information, please refer to our Material Safety Data Sheet (MSDS)

