



More than colour

## CHROMATIC NC WOOD LACQUER

**PRODUCT DESCRIPTION AND USES:**

Chromatic NC Wood Lacquer is a fast-drying nitrocellulose based high gloss enamel varnish ideal for protection and decoration of interior wood, skirting boards, timber and furniture. It produces a tough finish on timber surfaces and is easy to apply.

**SURFACE PREPARATION:**

new surface: Ensure surface is finely sanded, dried, cleaned and free from wax, grease, oil and other contaminants. Apply Chromatic sanding Sealer and sand it down before applying Chromatic NC Wood Lacquer.  
Previously painted surfaces: ensure surfaces are sanded properly, dried and cleaned prior to application of a new coat of Chromatic NC Wood Lacquer.

**PRIMER:**

sanding sealer

**APPLICATION:**

by spray. Apply 2 coats and ensure that preceding coat is thoroughly dry and there should be sanding between coats.

**THINNING:**

standard thinner

**DRYING TIME:**

touch dry 15 min

**FINISH:**

Gloss and matt

**MIXING:**

1 part of lacquer with 1 part of standard thinner by volume

**PACK SIZES:**

1/2L ,1L and 4L

## DISCLAIMER

The recommendations contained herein are given in good faith and meant to guide the user in accordance with good painting practices. They are gained from our tests and experiences and are believed to be accurate and reliable.

No warranty/guarantee is implied by the recommendations contained herein since the conditions of use; application method, substrate and cleanliness of the substrate are beyond the control of Chromatic Paints Uganda.

Technology may change with time, necessitating changes to this Technical Data Sheet (TDS). Chromatic Paints Uganda reserves the right to amend the TDS without any further notice. It is the responsibility of the user to ensure that the latest TDS is being used for reference

For health & safety information, please refer to our Material Safety Data Sheet (MSDS)

