



More than colour

CHROMATIC ONE PACK EXTERIOR VARNISH

PRODUCT DESCRIPTION AND USES:

Chromatic one pack exterior varnish is a single component, polyurethane alkyd based varnish ideal for use on external woodwork such as gates, furniture, fences, ornaments, etc. It provides good weatherability, flexibility, a perfect outdoor durability with good yellowing and high abrasion resistance. It combines performance and ease of application. and is easy to apply

SURFACE PREPARATION:

Timber surfaces are known to be porous, ensure that the timber to be varnished is clean, dry and free from any contaminants like dust, grease, oil, wax etc. for previously varnished timber, sand down thoroughly to bare wood, before applying 2 coats one pack exterior varnish. Application of 3-4 coats of Chromatic One Pack Exterior Varnish are recommended for new surfaces.

BENEFITS & FEATURES:

- Provides good outdoor durability
- Very high abrasion resistance
- Good yellowing resistance

FINISH:

full gloss and matt

APPLICATION:

By brush or spray

SPREADING CAPACITY:

Approximately 12-14m² per litre. Dependent on the surface profile and porosity or type of timber

THINNING & MIXING:

Chromatic White Spirit for brushing, chromatic Enamel Thinner for spraying

DRYING TIME:

Touch dry 3-5 hours. Thorough dry 8 hours. Recoatable in 16 hours

COLOUR RANGE:

As per chromatic Woodlac shade card. (the final Colour is dependent on the type of timber used).

EQUIPMENT CLEANING:

Clean equipment with White Spirit.

PACK SIZES:

1 Litre and 4 Litres

DISCLAIMER

The recommendations contained herein are given in good faith and meant to guide the user in accordance with good painting practices. They are gained from our tests and experiences and are believed to be accurate and reliable.

No warranty/guarantee is implied by the recommendations contained herein since the conditions of use; application method, substrate and cleanliness of the substrate are beyond the control of Chromatic Paints Uganda.

Technology may change with time, necessitating changes to this Technical Data Sheet (TDS). Chromatic Paints Uganda reserves the right to amend the TDS without any further notice. It is the responsibility of the user to ensure that the latest TDS is being used for reference

For health & safety information, please refer to our Material Safety Data Sheet (MSDS)

