



More than colour

CHROMATIC RUBBING COMPOUND

PRODUCT DESCRIPTION AND USES:

Chromatic Rubbing Compound is an excellent product for removing oxidation and imperfections from the surface of an older paint job. To eliminate fine scratches from the paint work. It generally breathes new life to old paint works of the car

SUBSTRATE:

steel, galvanised, iron, aluminium, fibreglass, concrete and wood

FINISH:

Matt

APPLICATION:

use of a micro fibre cloth or polishing pad

MIXING RATIO:

Mix one part of the compound with one part of water by volume.

DRYING TIME:

Touch dry is 5-10 mins

PACK SIZES:

1L and 4L

DISCLAIMER

The recommendations contained herein are given in good faith and meant to guide the user in accordance with good painting practices. They are gained from our tests and experiences and are believed to be accurate and reliable.

No warranty/guarantee is implied by the recommendations contained herein since the conditions of use; application method, substrate and cleanliness of the substrate are beyond the control of Chromatic Paints Uganda.

Technology may change with time, necessitating changes to this Technical Data Sheet (TDS). Chromatic Paints Uganda reserves the right to amend the TDS without any further notice. It is the responsibility of the user to ensure that the latest TDS is being used for reference

For health & safety information, please refer to our Material Safety Data Sheet (MSDS)

