



More than colour

## CHROMATIC SANDING SEALER

**PRODUCT DESCRIPTION AND USES:**

Chromatic sanding sealer is a nitrocellulose based semi matt sanding sealer, suitable for use as a base coat or first coat on interior and exterior wood. This specially designed material is intended for filling of grain on all interior solid timber or veneers prior to over coating with the appropriate varnish.

**SURFACE PREPARATION:**

Ensure the wood is dry, firm, clean and free of contaminants. Then, sand wood surfaces to a smooth finish with 150 grit sand paper.

**GLOSS LEVEL:**

(12% at 60°C Gloss Head)

**SOLIDS (BY WEIGHT):**

Approx. 17 %

**SOLIDS (BY VOLUME):**

12,3 %

**FINISH:**

Semi Matt

**APPLICATION:**

Brush or spray (airless or conventional)

**THINING:**

Thin with Chromatic standard Thinner

**DRYING TIME:**

Touch Dry: 5-15 minutes at 23°C Hard Dry: 2hours at 25°C

**COLOUR RANGE:**

clear

**SPREADING CAPACITY:**

Approximately 5-7M<sup>2</sup> per litre but can vary depending on the wood texture and porosity.

**PACK SIZES:**

½ ltr ,1 litre, 4 litres

## DISCLAIMER

The recommendations contained herein are given in good faith and meant to guide the user in accordance with good painting practices. They are gained from our tests and experiences and are believed to be accurate and reliable.

No warranty/guarantee is implied by the recommendations contained herein since the conditions of use; application method, substrate and cleanliness of the substrate are beyond the control of Chromatic Paints Uganda.

Technology may change with time, necessitating changes to this Technical Data Sheet (TDS). Chromatic Paints Uganda reserves the right to amend the TDS without any further notice. It is the responsibility of the user to ensure that the latest TDS is being used for reference

For health & safety information, please refer to our Material Safety Data Sheet (MSDS)

