



More than colour

CHROMATIC SUPER GLOSS ENAMEL

PRODUCT DESCRIPTION AND USES:

Chromatic Super Gloss Paint is a premium quality high gloss enamel-based paint that can be used on multi-surfaces. It is designed to provide maximum durability with excellent gloss retention. Its formulation delivers excellent flexibility, opacity and light-fast (non-fading) finish. It is suitable for use under most conditions including high humidity and areas with high rainfall. Chromatic Super Gloss Paint can be used both internally and externally on wood, metal, plaster, wallboards, stone or brickwork Chromatic Super Gloss Paint should be applied over appropriately primed and undercoated surfaces.

SURFACE PREPARATION:

NEW UNPAINTED SURFACES:

Surfaces should be clean, dry and free of any loose and flaky materials. Apply one coat of Chromatic Redoxide metal Primer and then two coats Chromatic Super Gloss Paint. Allow overnight drying between each coat.

PREVIOUSLY PAINTED WALLS:

Surfaces should be clean, dry and free of any loose and flaky materials. Apply one coat of an appropriate Primer then apply two coats of Chromatic Super Gloss Paint. Allow overnight drying between coats.

FINISH:

Gloss

APPLICATION:

Apply by brush, roller or spray; Use Chromatic white Spirit for application by brush, and Chromatic Enamel Thinner for spray application.

THINING & MIXING:

Thin with Chromatic White Spirit 10 - 20%. Note: Avoid over-thinning as this affects hiding power.

EQUIPMENT CLEANING:

Clean the equipment immediately after use with Chromatic White Spirit.

DRYING TIME:

Touch dry in 3 hours. Re-coatable after 14 hours..

COLOUR RANGE:

Over 3000 shades

SPREADING CAPACITY:

13 - 15m² per litre on a smooth surface at 30 - 40 microns DFT.

PACK SIZES:

1 litre, 4 litres, 20 litres.

DISCLAIMER

The recommendations contained herein are given in good faith and meant to guide the user in accordance with good painting practices. They are gained from our tests and experiences and are believed to be accurate and reliable.

No warranty/guarantee is implied by the recommendations contained herein since the conditions of use; application method, substrate and cleanliness of the substrate are beyond the control of Chromatic Paints Uganda.

Technology may change with time, necessitating changes to this Technical Data Sheet (TDS). Chromatic Paints Uganda reserves the right to amend the TDS without any further notice. It is the responsibility of the user to ensure that the latest TDS is being used for reference

For health & safety information, please refer to our Material Safety Data Sheet (MSDS)

