



More than colour

CHROMATIC UNIVERSAL UNDERCOAT

PRODUCT DESCRIPTION AND USES:

Chromatic Universal High Opacity Undercoat is an alkyd based, general purpose product specially formulated to provide a flexible, non-absorbent base and can be over coated by both oil and water-based topcoats. It is an intermediate coating applied between a primer and top coat because it works up excellent adhesion between primer and top coat especially if changing from a solvent based to water-based paint. It has excellent hiding power and because of this, it provides additional film to facilitate changing from dark to light colours, and will fill minor cracks and other blemishes. It is suitable for interior and exterior use and can be applied on wood, metal, plaster, stone etc.

SURFACE PREPARATION:

New Primed Metal, Wood or Plaster etc. surface MUST be clean and dry. Apply appropriate primer before applying on coat of universal undercoat. Allow 16 hours drying before overcoating.

PREVIOUSLY PAINTED - UNSOUND SURFACES:

Surface must be clean and dry, free from any loose or flaky materials and any other contaminants/defects. Patch affected areas with appropriate primer. Then slightly abrade the surface to give enhanced adhesion. Apply 1 coat of Chromatic Universal Undercoat. Allow 16 hrs of drying before applying appropriate topcoat

PREVIOUSLY PAINTED - SOUND:

Lightly sand surfaces. Ensure the surface is clean and apply 1 coat of Universal Undercoat and then allow 16 hours drying time, then appropriate topcoat is applied.

FINISH:

Matt

APPLICATION:

By brush, roller or spray

THINING & MIXING:

Use Chromatic White Spirit.

EQUIPMENT CLEANING:

Clean equipment immediately after use with Chromatic White Spirit.

DRYING TIME:

overcoat after 16 hours

COLOUR RANGE:

White

SPREADING CAPACITY:

9-13m² per litre

PACK SIZES:

1 Litre, 4 Litres and 20 Litres

DISCLAIMER

The recommendations contained herein are given in good faith and meant to guide the user in accordance with good painting practices. They are gained from our tests and experiences and are believed to be accurate and reliable.

No warranty/guarantee is implied by the recommendations contained herein since the conditions of use; application method, substrate and cleanliness of the substrate are beyond the control of Chromatic Paints Uganda.

Technology may change with time, necessitating changes to this Technical Data Sheet (TDS). Chromatic Paints Uganda reserves the right to amend the TDS without any further notice. It is the responsibility of the user to ensure that the latest TDS is being used for reference

For health & safety information, please refer to our Material Safety Data Sheet (MSDS)

