

CHROMATIC VINYL MATT EMULSION

PRODUCT DESCRIPTION AND USES:

Chromatic Vinyl Matt Emulsion is a premium quality copolymer-based emulsion paint that gives a rich luxurious matt finish with high durability, maximum protection on interior and exterior surfaces. Its rich high opacity smooth matt leaves

no brush marks on application.

Chromatic Matt Emulsion can be used on all types of new and previously painted surfaces i.e. plaster, concrete, building

boards, hardboard and bricks

SURFACE PREPARATION: New Plaster or Concrete

For priming apply 1 coat of Chromatic Plaster primer or 02 coats of Chromatic Budget Emulsion Undercoat thinned with

water to normal working consistency.

Previously painted walls

Old paint coatings, loose particles or distemper should be removed by wire brush or scrapping and anything remaining in the pores should be bound using 2 coats of Chromatic penetrating primer and left to dry prior to application of

Chromatic Vinyl Matt Emulsion.

Previously painted walls should be sanded down and 2 coats of

Chromatic Vinyl Matt Emulsion applied.

APPLICATION: By brush, roller or spray

DRYING TIME: Recoatable after 4 hours

FINISH: Matt

EQUIPMENT CLEANING: Clean the equipment immediately with water

THINNING & MIXING: Thin with clean tap water

COLOUR RANGE: Over 3000 house shades

SPREADING CAPACITY: 10 to 14 m² per litre at 40 microns DFT

PACKING: 20 Litre, 4Llitre

DISCLAIMER

The recommendations contained herein are given in good faith and meant to guide the user in accordance with good painting practices. They are gained from our tests and experiences and are believed to be accurate and reliable.

No warranty/guarantee is implied by the recommendations contained herein since the conditions of use; application method, substrate and cleanliness of the substrate are beyond the control of Chromatic Paints Uganda.

Technology may change with time, necessitating changes to this Technical Data Sheet (TDS). Chromatic Paints Uganda reserves the right to amend the TDS without any further notice. It is the responsibility of the user to ensure that the latest TDS is being used for reference

For health & safety information, please refer to our Material Safety Data Sheet (MSDS)



