



More than colour

CHROMATIC VINYL SILK EMULSION

PRODUCT DESCRIPTION AND USES:

Chromatic Vinyl Silk is a superior co-polymer emulsion paint formulated with the finest quality pigments to deliver good stain resistance, a fashionable silky and tough finish. Its unrivalled washability makes it ideal for interior use in high traffic areas like stores, passage ways, kitchens, bathrooms, corridors, office complexes, hospitals, food processing plants etc.

SURFACE PREPARATION:

New unpainted walls; Apply one coat of chromatic Vinyl Matt Emulsion then two coats of Chromatic Vinyl Silk Emulsion. Previously painted walls; Remove loose, flaking and powdery paint. If necessary porous walls should be primed with two coats of Chromatic Acrylic Binder then apply two to three coats of Chromatic Vinyl Silk Emulsion.

BENEFITS & FEATURES:

- silky sheen finish
- exceptional toughness
- washable
- excellent colour retention
- good opacity
- easy application
- Low VOC (VOC: < 50 g/L)
- Lead Free

APPLICATION:

By brush, roller or spray

SHADES:

White only

DRYING TIME:

Recoat after 4 hours

FINISH:

Silky Sheen Finish

THINNING & MIXING:

Thin with clean tap water

SPREADING CAPACITY:

10 to 14 m² per litre. (This varies depending on the nature surface.)

PACKING:

20 Litre, 4Litre

COLOUR RANGE:

Available in selected pastel shades from Chromatic in-house colors and BS 4800

DISCLAIMER

The recommendations contained herein are given in good faith and meant to guide the user in accordance with good painting practices. They are gained from our tests and experiences and are believed to be accurate and reliable.

No warranty/guarantee is implied by the recommendations contained herein since the conditions of use; application method, substrate and cleanliness of the substrate are beyond the control of Chromatic Paints Uganda.

Technology may change with time, necessitating changes to this Technical Data Sheet (TDS). Chromatic Paints Uganda reserves the right to amend the TDS without any further notice. It is the responsibility of the user to ensure that the latest TDS is being used for reference

For health & safety information, please refer to our Material Safety Data Sheet (MSDS)

