



More than colour

CHROMATIC WOODLAC EXTERIOR VARNISH

PRODUCT DESCRIPTION AND USES:

Chromatic woodlac exterior varnish is a semi-transparent coating designed for uniqueness, high durability and flexibility. It's highly flexible alkyd formulation makes it suitable for exterior softwood and hardwood timber applications for it provides a high level of UV resistance, water proofing, preservation, a long lasting finish resistant to cracking, peeling and blistering enhancing the natural beauty of the wood. Chromatic woodlac exterior is a technically advanced finish, which provides long term protection for exterior woodwork. It is suitable for most types of exterior hard and softwoods and may be used on external doors, window frames and wood cladding. It may be applied to bare or previously varnished wood after appropriate preparation. Chromatic woodlac exterior may also be used to refresh previously stained wood without darkening the effect. Chromatic woodlac exterior advanced formulation provides extremely durable and flexible finish. The flexibility is maintained when exposed to weathering giving the varnish excellent resistance to cracking, peeling and blistering. Chromatic woodlac exterior provides a rich, mellow finish which enhances the natural beauty of the wood. It may darken the color of bare wood.

SURFACE PREPARATION:

Timber surfaces are known to be porous, ensure that the timber to be varnished is clean, dry and free from any contaminants like dust, grease, oil, wax etc. for previously varnished timber, sand down thoroughly to bare wood, before applying 2 coats woodlac exterior varnish.

SPREADING CAPACITY:

8-12sq metres per litre (depending on the type of timber used.)

THINNING:

product ready for use, do not thin

COLOUR RANGE:

Clear. Also available As per chromatic Woodlac shade card. (the final Colour is dependent on the type of timber used).

FINISH:

Glossy

DRYING TIME:

Allow 6hrs drying time per coat. Drying times will vary dependent upon prevailing temperature, humidity and the substrate.

EQUIPMENT CLEANING:

Clean equipment with White Spirit.

APPLICATION:

brush, lint free cloth or by a dipping process.

PACK SIZES:

4 litres, 1 litre

DISCLAIMER

The recommendations contained herein are given in good faith and meant to guide the user in accordance with good painting practices. They are gained from our tests and experiences and are believed to be accurate and reliable.

No warranty/guarantee is implied by the recommendations contained herein since the conditions of use; application method, substrate and cleanliness of the substrate are beyond the control of Chromatic Paints Uganda.

Technology may change with time, necessitating changes to this Technical Data Sheet (TDS). Chromatic Paints Uganda reserves the right to amend the TDS without any further notice. It is the responsibility of the user to ensure that the latest TDS is being used for reference

For health & safety information, please refer to our Material Safety Data Sheet (MSDS)

