

CHROMATIC ZINC CHROMATE FREE METAL PRIMER

PRODUCT DESCRIPTION AND USES:	Chromatic Zinc Chromate free Metal Primer is an anti-corrosive primer used on bare metal surfaces exposed to mild/moderate environment. Chromatic Zinc Chromate free Metal Primer is especially suitable for protection of iron and steelwork exposed to humid air and salt spray.
SURFACE PREPARATION:	Surfaces must be cleaned before priming. Sand blasting is recommended. Wire brushing may be used for small jobs where only mild corrosion is evident.
FINISH:	Matt
APPLICATION:	By brush, baby roller or spray gun
THINING & MIXING:	Use Chromatic White Spirit for brush application and Chromatic Standard Thinner for spray application
EQUIPMENT CLEANING:	Clean equipment immediately after use with Chromatic White Spirit.
DRYING TIME:	Hard Dry after 24 hours. Suitable for over coating after 16 hours.
COLOUR RANGE:	Green, Blue, Yellow. Other colors available on request.
SPREADING CAPACITY:	8-10m ² per litre at 35 to 40 microns DFT
PACK SIZES:	1 Litre, 4 Litres and 20 Litres



DISCLAIMER

The recommendations contained herein are given in good faith and meant to guide the user in accordance with good painting practices. They are gained from our tests and experiences and are believed to be accurate and reliable.

No warranty/guarantee is implied by the recommendations contained herein since the conditions of use; application method, substrate and cleanliness of the substrate are beyond the control of Chromatic Paints Uganda.

Technology may change with time, necessitating changes to this Technical Data Sheet (TDS). Chromatic Paints Uganda reserves the right to amend the TDS without any further notice. It is the responsibility of the user to ensure that the latest TDS is being used for reference

For health & safety information, please refer to our Material Safety Data Sheet (MSDS)

