



More than colour

CHROMATIC WOOD PRESERVATIVE

PRODUCT DESCRIPTION AND USES:

Chromatic wood preservative is a solvent-based with nitrocellulose, modified alkyd resins and additives. It is a wood preservative treatment for untreated and bare timber that offers microporous protection against wood rot, fungi, decay, mould and insect attack. Its available in clear and a range of attractive wood tone colours. It highlights the weathering process and prevents future damage for old wood

SURFACE PREPARATION:

Wood should be sanded down to a clean sound surface and remove dust by wiping with chromatic white spirit

FINISH:

Matt

APPLICATION:

Apply thinly and evenly using a synthetic brush designed for solvent borne products. Ensure end grain is thoroughly treated along with cut and drilled areas. it is recommended that a minimum of 2 coats are applied depending on wood or wood is dipped into the preservatives.

DRYING TIME:

12 hours under normal conditions (touch dry)

COLOUR RANGE:

Available in limited wood colours.

SPREADING CAPACITY:

Up to 6sqm per litre

PACK SIZES:

5 Litre and 20 litre

DISCLAIMER

The recommendations contained herein are given in good faith and meant to guide the user in accordance with good painting practices. They are gained from our tests and experiences and are believed to be accurate and reliable.

No warranty/guarantee is implied by the recommendations contained herein since the conditions of use; application method, substrate and cleanliness of the substrate are beyond the control of Chromatic Paints Uganda.

Technology may change with time, necessitating changes to this Technical Data Sheet (TDS). Chromatic Paints Uganda reserves the right to amend the TDS without any further notice. It is the responsibility of the user to ensure that the latest TDS is being used for reference

For health & safety information, please refer to our Material Safety Data Sheet (MSDS)

