

CHROMATIC FLOURESCENT PAINT

PRODUCT DESCRIPTION AND USES:

Chromatic fluorescent paint is a highly visible day time coating or when use under lights at night.

Chromatic fluorescent paint is ideal for use on skips, bollards, bridges, signages, and to identify any hazardous objects. It is also used by sign writers, stage crews and artists. It is

recommended to apply a minimum of two coats.

SURFACE PREPARATION:

All surfaces must be clean, dry, sound and free from oils and

contaminants

FINISH: Sheen

APPLICATION: By brush, roller or spray

DRYING TIME: touch dry 3 Hours, Hard dry 12 hours, Recoatable after 4 hours

COLOUR RANGE: blue, lemon yellow, light orange, orange red, red, green, purple.

SPREADING CAPACITY: 11 - 14 square meters per litre

PACK SIZES: 1L and 1/2L

APPLICATION: By brush, roller or spray

Fluorescent paint will fade over time due to its fluorescent nature. As a result, this product is not recommended for large areas, whole busses or other vehicles as the product will

become patchy over time

DISCLAIMER:

DISCLAIMER

The recommendations contained herein are given in good faith and meant to guide the user in accordance with good painting practices. They are gained from our tests and experiences and are believed to be accurate and reliable.

No warranty/guarantee is implied by the recommendations contained herein since the conditions of use; application method, substrate and cleanliness of the substrate are beyond the control of Chromatic Paints Uganda.

Technology may change with time, necessitating changes to this Technical Data Sheet (TDS). Chromatic Paints Uganda reserves the right to amend the TDS without any further notice. It is the responsibility of the user to ensure that the latest TDS is being used for reference

For health & safety information, please refer to our Material Safety Data Sheet (MSDS)







